DUCHESNE COUNTY MONUMENT SURVEY RECORD

80.00

00°10'45'

5/8"X24" REBAR WITH A 2½" DIA. ALUMINUM DUCHESNE COUNTY MONUMENT AT 1/4 CORNER

Y NAIL AND WASHER ON LEFT SIDE OF "H" BRACE POST

5/8"X24" REBAR WITH A 21/2"


DIA. ALUMINUM DUCHESNE COUNTY MONUMENT AT SECTION CORNER

55.30.00%

5/8"X24" REBAR WITH A 21/2"
DIA. BRASS DUCHESNE COUNTY
MONUMENT AT SECTION CORNER

T1S R1W 1/4 SEC 18+SEC 17

U.S.B.&M.



NORTH SCALE: 1"=30'

0'

30'

"X" CHISELED N 84°30'05" W
IN CONCRETE 35.45' WATER BOX s 76°40′56" W NAIL AND WASHER ON RIGHT SIDE OF F POWER POLE 65.49 N 62.09,45, E 2642.01 FENCE CORNER

NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED
FROM G.P.S. OBSERVATIONS AT A CONTROL POINT
(SECTION CORNER) LOCATED AT LAT. 40"23"20.57790"N
AND LONG. 110"01"46.98583"W USING THE UTAH STATE
G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK
MAINTAINED AND OPERATED BY THE AUTOMATED
GEOGRAPHIC REFERENCE CENTER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND A COPPER WELD AT THE POSITION OF THE 1/4 CORNER



SET A 5/8" X 24" REBAR WITH A 2½" ALUMINUM DUCHESNE COUNTY MONUMENT AT THE POSITION OF 1/4 CORNER AFTER ROAD CONSTRUCTION

2018

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7316449.121 E: 2049895.544 NAVD88 EL: 5742.06'

40°23'46.67814" N LATITUDE: LONGITUDE: 110°01'47.09266" W

ELLIPSOID HEIGHT: 5687.54

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0010W0_200440

CERTIFICATION

Jerry D. Allred _ , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>28 FEB 2018</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

